

FACILITY/PRODUCT PROTECTION

Full Dome Mirror-360° View

4-way intersections or large area, panoramic viewing-ceiling mount. Furnished with mounting holes drilled in flange. For indoor use only.



ITEM	Diameter	Price
AV18FL-B	18"	\$79.00
AV26FL-B	26"	\$120.00
AV32FL-B	32"	\$167.00
AV36FL-B	36"	\$207.00
AV48FL-B	48"	\$300.00

Half Dome Mirror-180° View

3-way "I" intersections - wall or ceiling mount. Furnished with mounting holes drilled in flange. For indoor use only.



ITEM	Diameter	Price
AV12HL-B	12"	\$28.00
AV18HL-B	18"	\$44.00
AV26HL-B	26"	\$67.00
AV32HL-B	32"	\$94.00
AV36HL-B	36"	\$117.00

Quarter Mirror-90° View

2-way "L" intersections -corner, wall or ceiling mount. Furnished with mounting holes drilled in flange. For indoor use only.



ITEM	Diameter	Price
AV12QL-B	12"	\$15.00
AV18QL-B	18"	\$23.00
AV26QL-B	26"	\$35.00
AV32QL-B	32"	\$48.00
AV36QL-B	36"	\$62.00

Convex Mirror

For general wide-angle viewing. Waterproof painted hard-board backing with heavy extruded rubber rims.



ITEM	Diameter	Price
P-120-B	12"	\$32.00
P-180-B	18"	\$46.00
P-260-B	26"	\$80.00
P-300-B	30"	\$105.00
P-360-B	36"	\$134.00

- 160° + actual viewing angle.
- For indoor or outdoor use.
- Equipped with adjustable swivel and mounting bracket for infinite adjustment.
- Recommended mounting height: 8 to 10 feet.
- Choose a mirror with the lens and backing materials best suited to your application.

Roundangular Mirror

Excellent for low ceilings. Painted hardboard backing.



ITEM	Size	Price
P1218-B	12" x 18"	\$54.00
P1826-B	18" x 26"	\$96.00
P2030-B	20" x 30"	\$122.00
P2436-B	24" x 36"	\$160.00

Fork Blade Protectors



- Protect Packages and Skids from Sharp Edges of Fork Lift blades
- 100% Polyethylene
- Yellow Colour for high visibility
- Easily Removable

42" Fork Blade Protectors
FBP442-A **\$75⁰⁰**

48" Fork Blade Protectors
FBP448-A **\$75⁰⁰**

Electronic Code Switch



Keep unauthorized personnel from operating the lift truck.

The Electronic Code Switch can track up to 15 drivers, preventing unauthorized vehicle use. If an accident

occurs and the vehicle is damaged, the last driver can easily be identified.

An alarm can also be programmed when maintenance is due.

Electronic Code Switch
SY31214-C **\$179⁰⁰**



PREVENT UNAUTHORIZED USE

VOLTAGE INPUT

12-90VDC
Correct voltage level must be set with DIP switches on the rear of the ECS

OUTPUT

Relay contact rating: 6AMP continuous
-10 (5 Sec.) for bigger loads, an external relay must be used

CURRENT USE

10mA when relay is not activated, less than 60mA in activated operation